Bakery Line Single

Compressor cooling





Product description

Bakery Line Single is manufactured for the distribution of cold bakery products. The box is made according to the standard dimensions of bakery trays. The box is designed with ScanBox ExP construction that combines optimized insulation performance with high operational reliability and environmentally conscious choices.

The box is equipped with compressor cooling that provides effective cooling down to 3°C in 30 minutes. Digitally adjustable temperatures ensure excellent

food quality control. ScanBox Bakery Line Single has capacity for 12 baking trays according to the standard dimensions of 400x600 or 450x600.

Equipped with ScanBox Digital Control, excenter lock, solid door, 160 mm lockable wheels, removable 'L' shaped runners with 100 mm spacing, black RAL 9005, 220-230V single phase with Type F electrical plug. The equipment can be easily adapted as required through available extra options.





Technical specification

MODEL SERIE: Bakery Line Single - Compressor cooling



Product models	BBSCC40	BBSCC45		
Properties				
Regulator	Digital	Digital		
Cooling system	Compressor back mounted (std)	Compressor back mounted (std)		
Capacity				
Tray system	400x600 450x600	400x600 450x600		
Distance between racks (mm)	100	100		
Number of 65mm trays	12	12		
Maximum load weight per rack (kg)	9	9		
Distance to the first rack (mm)	20	20		
Physical Attributes				
Inside depth (mm)	681 mm	681 mm		
Inside width (mm)	487 mm	487 mm		
Inside height (mm)	1287 mm	1287 mm		
Outside depth (mm)	950 mm	950 mm		
Outside width (mm)	675 mm	675 mm		
Outside height (mm)	1677 mm	1677 mm		
Volume (I)	427	427 I		
Net weight (kg)	94 kg	94 kg		
Spiral Cord	4.5 m	4.5 m		
Electrical Attributes				
Rated voltage (V)	220-240V / 1 phase	220-240V / 1 phase		
Rated frequency (Hz)	50-60 Hz	50-60 Hz		
Power Rating (A)	1.55 A	A		
Power (W)	180 W	180 W		
IP code	22	22		



Equipment & Accessories

MODEL SERIE: Bakery Line Single - Compressor cooling



Castors & Brakes

1000003	Castors 160 mm swiveling with brake
1000007	Castors 160 mm, stainless steel, swiveling with brake
1000009	Castors 160 mm, all swiveling w. brakes
1000010	Castors 160 mm, stainless steel, all swiveling w. brakes
1000016	Castors 200 mm w. central brake
1000008	Castors 160 mm, dish washable w. brake
1000004	Castors 200 mm swiveling with brake
1000005	Castors 160 mm reinforced, swiveling with brake
1000015	Castors 160 mm w. central brake
1000006	Castors 200 mm reinforced, swiveling with brake
1000017	Castors 160 mm stainless steel w. central brake

Electric System

898294-1	220-240V - Type K
905390	220-240V - Type H
4000556	220-240V - Type L
898208-1	220-240V - Type J
90001	220-240V - Type C
898205-1	220-240V - Type G
905817	220-240V - Type I
898202-1	220-240V - Type G 1,5mm ²
90004	220-240V - Type O
898201-1	220-240V - Type CEE 7/7
898203-1	220-240V - Type I
90002	220-240V - Type D
4000241	220-240V - Type M

Exterior	
303010-2	Signature Logo
302030-1	Grey (RAL 7042)
950001	Signature Cover
302020-1	Red (RAL 3003)
302040-1	Black (RAL 9005)
Door	
93002	Glass window
93001	Solid
Logistic System	
361020	Central Brake
302002-2	Tow Bar Stainless Steel
302001-3	Tow Bar VE
Door Handle	
Default	Excenter Lock
Accessories	

Card Holder

400010-1

www.scanbox.se

