Stackable Box Single

Static heating





Product description

Portable Line Single is made to hold and transport hot food easily and safely. The box is designed with ScanBox ExP construction that combines optimized insulation performance with high operational reliability and environmentally conscious choices.

The box is equipped with a static heating system that provides stable heating by natural convection and has an operating temperature of 80°C. Adjustable

ventilation ensures excellent food quality control. ScanBox Portable Line has capacity for 4 containers in the GN 1/1 standard.

Equipped with excenter lock, solid door, removable U-guide rails with 80 mm spacing, black RAL 9005, as standard. The equipment can be easily adapted as required through the available extra options.



Technical specification

MODEL SERIE: Stackable Box Single - Static heating



Product models	SBSHS04
Capacity	
Tray system	GN 1/1
Distance between racks (mm)	80
Number of 65mm trays	4
Maximum load weight per rack (kg)	9
Distance to the first rack (mm)	65
Physical Attributes	
Inside depth (mm)	567 mm
Inside width (mm)	352 mm
Inside height (mm)	407 mm
Outside depth (mm)	693 mm
Outside width (mm)	459 mm
Outside height (mm)	513 mm
Volume (I)	81 I
Net weight (kg)	20 kg
Electrical Attributes	
IP code	44



Equipment & Accessories

MODEL SERIE: Stackable Box Single - Static heating



Exterior	
Default	Black (RAL 9005)
303010-2	Signature Logo
302030-1	Grey (RAL 7042)
950001	Signature Cover
302020-1	Red (RAL 3003)

Door		
Default	Solid	
Door Handle		
Default	Excenter Lock	
Accessories		

Electric System	
Default	220-240V - Type CEE 7/7
898294-1	220-240V - Type K
905390	220-240V - Type H
4000556	220-240V - Type L
898208-1	220-240V - Type J
90001	220-240V - Type C
898205-1	220-240V - Type G
905817	220-240V - Type I
898202-1	220-240V - Type G 1,5mm²
90004	220-240V - Type O
898203-1	220-240V - Type I
90002	220-240V - Type D
4000241	220-240V - Type M

www.scanbox.se

